

# Aduro Vetrofix V

8133 000210

Retardant for the glass coating using a paint roller for **industrial and professional use**

## PRODUCT DESCRIPTION

**General** Special mixture of solvents to optimize the processability of the mixture Aduro Vetrocolor and ADLER Vetro PUR-Härter due to retarded drying, if glass elements have to be coated by paint roller.

### Application area




- As addition to Aduro Vetrocolor for coating glass elements.
- The product does not influence the surface quality of the coating system (chemical and mechanical resistance).
- Suitable for humid areas.

## PROCESSING

**Instructions for use**


- Aduro Vetrofix V must be incorporated carefully into the hardened varnish by stirring.
- Use a paint roller for application (short haired roller – see supplementary products).
- Please follow our „**Guidelines for glass coating with polyurethane paints for humid areas**“. Mixed varnish can be used as described in the relative technical data sheet.

### Quantity to be added




Mixing ratio:  
 100 percent by weight of Aduro Vetrocolor in the desired colour shade  
 + 20 percent by weight of ADLER Vetro PUR-Härter  
 + 10-20 percent by weight of Aduro Vetrofix V 8133 000210

### Pot life of the mixing



8 hours

### Cleaning the working equipment



With ADLER DD-Verdünnung (thinner) 80019 or ADLER Waschverdünnung 80077.

---

**ORDERING INFORMATION**

---

**Size of trading unit**

400 g


**Supplementary products**

Aduro Vetrocolor 2495  
ADLER Vetro PUR-Härter 8232 000210  
ADLER DD-Verdünnung 80019  
ADLER Waschverdünnung 80077  
Lackroller WL 10 cm 9645 811  
Lackroller WL 25 cm 9646 011

---

**FURTHER DETAILS**

---

**Durability / storage**

At least 1 year in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

**Safety-related information**

Please follow the associated safety data sheet, the latest version can be retrieved from the Internet at [www.adler-lacke.com](http://www.adler-lacke.com).

The product is only suitable for the industrial and professional use

---