


ADLER Ferroantik

41160



Product description

Water-thinnable matt special-effect paint on the basis of an acrylate emulsion for outdoor and indoor application with very good weathering resistance.

Field of application

Wrought ironwork such as fences, railings, crosses. Also suitable for refurbishing bonded old coats. **For rusty surfaces, we recommend ADLER Ferroblock 41108** (please refer to data sheet).

Application

Coating, rolling, spraying
(Spray nozzle diameter at least 2 mm!)

Primer

Zinc/aluminium:
1 x ADLER Acryl-Unigrund 41191 (please refer to data sheet)
Steel:
2 x ADLER Acryl-Unigrund 41191
Intermediate drying at least 4 hours

Topcoat

2 x ADLER Ferroantik 41160
Intermediate drying at least 4 hours
The design of the antique look only shows after the second coat. **No subsequent brushing necessary!**

Thinner

Water
Brushing 5 %, rolling 10 %, spraying 20 %

Working equipment

Clean working equipment with water immediately after use. Thoroughly dry spraying devices in order to avoid rusting. Remove dried-on residues with ADLER Abbeizer Rote Krähe 95125 (paint remover).

Application and object temperature

Not below + 10 °C
High air humidity and/or low temperatures tend to delay drying.

Drying time (room temperature 20 °C)

Repaintable after approx. 3 hours

Spreading rate

6 – 8 m²/l per coat

Packaging

375 ml, 750 ml, 2,5 l

Storage

Cool but frost-free

Continue

ADLER Ferroantik 41160

Storage stability

3 years in original, sealed containers

Colour

Anthracite

Safety information

Please pay attention to the safety information sheet!
Also when processing low-emission paint, conventional protective measures must be adhered to.