

## ADLER Haustürenpflegeset

51709

**System care kit for transparent and opaque coated front doors and garage gates for DIY and professional use**

### PRODUCT DESCRIPTION

#### General

The care kit for front doors contains 2 cleaning clothes, 2 sprayheads and the products ADLER Top-Cleaner and ADLER Door-Finish.

- **ADLER Top-Cleaner:** Cleaning product with high dirt dissolving and very good degreasing properties.
- **ADLER Door-Finish:** Care agent to remove spots and dust. The product forms a protective film against dirt and water, refreshes the surfaces and creates again a silky gloss.

#### Special properties and standards



- **French ordinance DEVL1104875A** regarding the marking of construction coating products for their emission of volatile pollutants: A+


#### Application areas




- For opaque or transparent coated front doors and garage gates.

### PROCESSING

#### Instructions for use



- Please shake the product before use.
- The temperature of the product and object, and the room temperature must be at least +15 °C.
- The treated surfaces must be sanded very well before any overpainting.
- We recommend applying ADLER Haustürenpflegeset twice a year.
- For ADLER Door-Finish please screw on the supplied spray head before use.

**Application technique**Yield per application  
(m<sup>2</sup>/l)

20

**The product is ready to use.**

The shape, the properties and moisture of the substrate affect the consumption/yield. Accurate values for consumption must be obtained by applying trial coats in advance.

**Drying times**

(at 23 °C and 50 % rel. humidity)



ADLER Door-Finish

after approx. 15 minutes

The figures given above are reference values. The drying time depends on the type of substrate, coat thickness, temperature, air exchange and relative atmospheric humidity.

Lower temperatures and/or high level of atmospheric humidity can increase the drying time.

**Cleaning the working equipment**

With warm water and soap immediately after use.

**SUBSTRATE****Type of substrate**

Front doors and garage gates, which were coated with one of the following products:

- Aquawood Protor-Finish L NG und D NG
- Aquawood DSL Q10 M
- ADLER Acryl-Spritzlack Q10 M
- Aquawood Protect

**Preparation of the substrate**

For deep cleaning apply **ADLER Top-Cleaner** on the entire, coated wooden parts using the cleaning cloth or spray it with the spray head screwed on. Rewashing with warm and clean water in order to remove bonded dirt.

**PRODUCT APPLICATION****Product application**

Spray ADLER Door-Finish on the entire, coated surface. After 10 minutes wipe the surface with a cleaning cloth. Repeat this procedure for a significant effect.

**ORDERING INFORMATION****Size of trading unit**

500 ml

**Color shades/degree of gloss**

Farblos

51700

**Supplementary products**


ADLER Reinigungstücher 96210  
ADLER Sprühköpfe 96220  
ADLER Top-Cleaner 51696  
ADLER Door-Finish 51700

---

## FURTHER DETAILS

---

### Durability/storage



At least 1 year in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

---

### Safety-related information



Please pay attention to the associated safety data sheet. The current version can be accessed on the Internet at [www.adler-lacke.com](http://www.adler-lacke.com).

---