Technical data sheet



ADLER Tiefengrund (primer), solvent-based

40944

















Product description

Solvent-based special primer with hardening depth effect for

exterior surfaces.

Alkali resistant, non-saponifiable, prevents splotchy drying of

full colours on plaster and brickwork.

Fields of application

Plaster, concrete, gympsium, lime sand bricks as well as as-

bestos cement.

Can also be used on old chalking coats.

For interior surfaces, we recommend water-thinnable ADLER

Tiefengrund (primer) 40905.

Application

Brushing (with a brush)

Surface pretreatment

Fresh plaster and concrete must be thoroughly dry. Remove

loose old coats. Correct cracks and irregularities.

Primer

1x with ADLER Tiefengrund (primer) 40944

Topcoat

2 x ADLER Acrylcolor (see technical data sheet) 40410 ff

Thinner

ADLER Adlerol free from aromatics 80301; Delivery form: ready for application, even out any evaporation losses with

ADLER Adlerol free from aromatics 80301.

Application and

object temperature

At least + 5 °C

Drying time

Paintable after approx. 8 hours

Working equipment

Clean with ADLER Adlerol free from aromatics 80301 imme-

diately after use.

Remove dried-on residue with ADLER Abbeizer (paint re-

mover) 95125.

Spreading rate (per coat)

6 - 9 m²/l per coat

Container sizes

750 ml, 5 l

Colour

Colourless 40944

Safety information

Please pay attention to the safety information sheet!

10-09 (replaces 01-07)

ADLER-Werk Lackfabrik, A-6130 Schwaz Fon: 0043/5242/6922-450, Fax: 0043/5242/6922-399, Mail: info@adler-lacke.com